

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/019382 A2

(51) International Patent Classification⁷: **H01L**
(21) International Application Number:
PCT/US2003/026428
(22) International Filing Date: 21 August 2003 (21.08.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
60/405,604 21 August 2002 (21.08.2002) US
(71) Applicant: SECUGEN CORPORATION [US/US];
2356 Walsh Ave., Santa Clara, CA 95051 (US).

(71) Applicants and

(72) Inventors: KIM, Jee-Hoon [KR/US]; 20380 Stevens
Creek Boulevard #204, Cupertino, CA 95014 (US).
SHIGETAKA, Akiba [JP/JP]; #419, 3-11-31, Ikejiri,
Setagaya-ku, Tokyo 154-0001 (JP). LEE, Dong, Won
[KR/US]; 20700 Fourth Street, Saratoga, CA 95070 (US).

(74) Agents: HODDER, Douglas, G. et al.; Morrison & Foer-
ster LLP, 755 Page Mill Road, Palo Alto, CA 94304 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: TFT SENSOR HAVING IMPROVED IMAGING SURFACE

(57) Abstract: Disclosed is an image capture sensor including a light detection transistor having a light sensitive layer which con-
ducts electricity in response to detection of a predetermined amount of light and a switch interconnected to the light detection tran-
sistor and responsive to detection of light by the light detection transistor. A glass substrate is layered over both the light detection
transistor and switch. The glass substrate provides a durable and smooth surface upon which a patterned object to be imaged in
placed.



WO 2004/019382 A2

TFT SENSOR HAVING IMPROVED IMAGING SURFACE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to provisional patent application serial number 60/405,604 filed August 21, 2002.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates generally to a imaging of a patterned object such as a fingerprint. More specifically, this invention relates to patterned object capture sensors including thin-film transistors.

Background

[0003] As known to those skilled in the art, fingerprint recognition is a kind of technology for granting an access authorization to systems such as a computer, an access control system, a banking system, etc. Fingerprint recognition systems are generally classified into two types: optic type system using a lens and a prism, and non-optic type system using a semiconductor or thin-film transistor (TFT), not a lens. A TFT fingerprint capture device is a kind of contact image sensor using photosensitivity of a-Si:H, and has high photosensitivity due to its relatively thin structure.

[0004] The structure of the fingerprint capture sensor is shown in Figure 1. Figure 1 is a vertical sectional view showing a unit cell of a conventional fingerprint capture sensor. Figure 1 illustrates a conventional thin film transistor (TFT) image acquisition sensor which may be used to image a fingerprint for use with equipment and software providing identity verification. Such an image acquisition device is disclosed in co-pending U.S. Patent Application Serial No. 10/014,290 filed December 10, 2001, which is hereby incorporated by reference in its entirety. Figure 1 is a sectional view showing a unit cell of a conventional fingerprint capture sensor. In the fingerprint capture sensor 10 a light sensing unit 12 and a switching unit 13 are horizontally arranged on a transparent substrate 11. Under the transparent substrate 11, a back light (not shown) irradiates light upward to be passed through

the fingerprint capture sensor 10. A source electrode 12-S of the light sensing unit 12 and a drain electrode 13-D of the switching unit 13 are electrically connected to each other through a first electrode 14. A gate electrode 12-G of the light sensing unit 12 is connected to a second electrode 15.

[0005] In the above structure, a photosensitive layer 12-P such as amorphous silicon (a-Si:H) is formed between the drain electrode 12-D and source electrode 12-S of the light sensing unit 12. Then, when more than a predetermined quantity of light is received, current flows through the drain electrode 12-D and the source electrode 12-S. Figure 2 illustrates how sensor 10 operates to capture a ridge 22 of a fingerprint 20. Light 24 generated from the back light under the transparent substrate 11 is reflected on a fingerprint pattern and received by the photosensitive layer 12-P of the light sensing unit 12, thus causing electricity to flow in the light sensing unit 12. Referring again to Figure 1, an upper surface ranging from the drain electrode 13-D to the source electrode 13-S is covered with a light shielding layer 13-sh such that external light cannot be received by the switching unit 13. Preferably, an insulating layer 17 is formed over first electrode 14 and a passivation layer 18 is formed over insulating layer 17. Passivation layer 18 can be formed of silicon-nitride (SiNx) and is provided to electrically and physically protect the remainder of capture sensor 10. As is understood by those skilled in the art, an array of capture sensors such as capture sensor 10 can be formed to image an entire fingerprint.

[0006] Regarding capture sensor 10, however, passivation layer 18 may not be durable enough to withstand many repeated uses of sensor 10. Additionally, it may be difficult to make the surface of passivation layer 18 relatively smooth. And, irregularities in the surface of passivation layer 18 can distort a fingerprint image which sensor 10 is acquiring.

BRIEF SUMMARY OF THE INVENTION

[0007] An image capture sensor in accordance with the present invention includes a glass layer on which an object to be imaged is placed. Unlike the passivation layer discussed above in the background section, a glass layer can be made thick enough to be relatively durable and is relatively smoother than the passivation layer of the prior art. Accordingly, an image capture sensor in accordance with the present invention includes a light detection transistor having a light sensitive layer which conducts electricity in response to detection of a predetermined amount of light and a switch interconnected to the light detection transistor and responsive to

detection of light by the light detection transistor. A glass substrate is layered over both the light detection transistor and switch. The glass substrate is the surface upon which a patterned object to be imaged is placed.

[0008] In another aspect of the invention, the glass substrate includes fiber-optic strands, allowing the glass substrate to be thicker and, thereby, advantageously more durable.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] Figure 1 is a sectional view of a prior art thin-film transistor object capture sensor which includes a light sensing transistor and a switch and which can be used to detect a patterned object such as a fingerprint.

[0010] Figure 2 is an illustration showing the operation of the object capture sensor shown in Figure 1.

[0011] Figure 3 is a sectional view of an object capture sensor including a glass substrate on which an object to be patterned is to be placed in accordance with the present invention.

[0012] Figure 4a is an illustration of the operation of the object capture sensor shown in

[0013] Figure 4b is an illustration showing detail of the operation of the object capture sensor shown in Figures 3 and 4a.

[0014] Figure 5 is a sectional view of a second embodiment of an object capture sensor including a conducting layer adjacent to a glass substrate on which an object to be patterned is to be placed in accordance with the present invention.

[0015] Figure 6 is a sectional view of a third embodiment of an object capture sensor - including fiber-optic strands in a glass substrate on which an object to be patterned is to be placed in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0016] An image capture sensor in accordance with the present invention is shown in Figure 3. Capture sensor 100 includes a passivation layer 118, which can be formed of SiNx. On top of passivation layer 118, a storage capacitor layer is formed including first electrode 115. This storage capacitor layer is preferably formed from indium tin oxide (ITO), which is conductive and transparent. On top first electrode 115, a insulating layer 117 is formed, preferably of SiNx. Over insulating layer 117, a second electrode 114 is formed, preferably of tin oxide. First electrode 115, insulating layer 117 and second electrode 114 together form the storage capacitor. Over second electrode 114, another insulating layer 116 is formed, which can be formed from SiNx. A layer of glass layer 111 is placed over insulating layer 116. A fingerprint to be imaged is placed on glass layer 111, which may be referred to herein as the imaging surface.

[0017] A light sensing unit 112, which is preferably a thin-film transistor, and a switching unit 113, which is also preferably a thin-film transistor, are horizontally arranged on a passivation layer 118. Under passivation layer 118, a back light 120 irradiates light upward to be passed through the fingerprint capture sensor 100. As shown in Figure 3, back light 120 is separated from a lower, exposed surface of passivation layer 118. It is also considered, however, that backlight 120 be placed against lower surface of passivation layer 118. Backlight 120 can be an LED or any other type of light source as is understood in the art. A source electrode 112-S of the light sensing unit 112 and a drain electrode 113-D of the switching unit 113 are electrically connected through second electrode 114. A gate electrode 112-G of the light sensing unit 112 is connected to first electrode 115. Additionally, a first light shielding layer 113-sh is placed between insulating layer 117 and passivation layer 118 at switching unit 113. As detailed below, first light shielding layer 113-sh blocks light from backlight 120 from reaching switching unit 113. Additionally, second light shielding layer 122 is positioned between glass layer 111 and insulating layer 116 at switching unit 113 to shield switching unit 113 from light passing through or reflected from glass layer 111.

[0018] In the above structure, a photosensitive layer 112-P such as amorphous silicon (a-Si:H) is formed between the drain electrode 112-D and source electrode 112-S of the light sensing unit 112. As is understood in the art, photosensitive layer 112-P allows current to flow in response to a predetermined amount of light striking a surface of photosensitive layer 112-P.

In this way, when more than a predetermined quantity of light is received at a surface of photosensitive layer 112-P, current flows through the drain electrode 112-D and the source electrode 112-S.

[0019] Figures 4a and 4b illustrate the operation of sensor 100 discussed above. Figure 4a illustrates a fingerprint 130 placed against glass layer 111. Figure 4b is a detailed view of a portion of Figure 4a showing a single ridge of fingerprint 130a placed against glass layer 111 of sensor 100. Light 150, generated from back light 120 beneath passivation layer 118, is reflected from fingerprint ridge 130a and received by the photosensitive layer 112-P of the light sensing unit 112, thus causing electricity to flow in the light sensing unit 112. Gate electrode 112-G of light sensing unit 112 serves to block light 150 directly emitted by light source 120 from reaching light sensing unit 112 through a lower face thereof. Additionally, as discussed above, a portion of switching unit 113 from the drain electrode 113-D to the source electrode 113-S is covered with a light shielding layer 113-sh such that external light cannot be received by the switching unit 113.

[0020] When light photosensitive layer 112-P of light sensing unit 112 allows current to flow, the current passes through electrode 114 and into drain electrode 113-D of switching unit 113. This causes switching unit 113 to be activated, thereby indicating that a portion of a fingerprint ridge is above the location of sensor 100 in a fingerprint sensor array (not shown). If a fingerprint valley is above the location of sensor 100, then incident light from backlight 120 will be reflected back into sensor 100 to a far smaller degree than if a ridge is above the location of sensor 100. As such, photosensitive layer 112-P will not receive sufficient light to begin conducting sufficient current to activate switching unit 113. In this way, an array of image capture sensors such as image capture sensor 100 can be used to determine the contours of fingerprint ridges and valleys of a fingerprint placed on the imaging surface of such an array.

[0021] As discussed above, a glass surface, which is relatively durable, is used as the imaging surface for capture sensor 100. As such a relatively high degree of protection is provided to the rest of capture sensor 100. Also, the glass imaging surface can be relatively smooth, causing relatively little distortion in a captured image. Additionally, no extra coating over the surface of a capture sensor in accordance with the present invention is necessary.

[0022] Referring again to Figure 3, in a method of fabricating capture sensor 100, a second light shielding layer 122 is first placed on glass layer 111 via evaporation, sputtering or any other method. Glass layer 111 is preferably between about 5 and 10 μm , though may be

either thicker or thinner. Light shielding layer 122 is preferably formed from a metal such as aluminum, but may be formed from any suitable light blocking material. Next, insulating layer 116 is formed on top of glass layer 111 and second light shielding layer 122. As noted above, insulating layer 116 is preferably formed from SiNx. Photosensitive layer 112-P is then formed over insulating layer 116. As discussed above, photosensitive layer 112-P is preferably formed from a-Si:H. Source electrode 112-D of light sensing unit 112, second electrode 114 and drain electrode 113-D of switching unit 113 are next formed over insulating layer 116. Source electrode 112-D, second electrode 114 and drain electrode 113-D are each preferably formed of ITO, but may be formed of any suitable conductor. Next, insulating layer 117 is formed and over insulating layer 117 first electrode 115 is formed. Insulating layer 117 is preferably formed from SiNx and first electrode 115 is preferably formed of ITO but may be formed of any suitable conductor. Next, gate electrode 112-G of light sensing unit 112 and light shield 113-sh are formed. Preferably, gate electrode 112-G and light shielding layer 113-sh are each formed of ITO, but may be formed of any suitable material and light shielding layer 113-sh does not need to be formed from the same material as gate electrode 112-G. Next, passivation layer 118, which is preferably formed from SiNx, is formed over first electrode 115, gate electrode 112-G and light shielding layer 113-sh. As discussed above, backlight 120 can either be attached to the lower, exposed surface of passivation layer 118 or separately supported in a known manner.

[0023] A second embodiment of an image capture sensor in accordance with the present invention is illustrated in Figure 5. Image capture sensor 200 has substantially the same structure as capture sensor 100 except that conductive ITO layer 230 is placed beneath glass layer 211 and an insulating layer 232, which can be formed of SiNx, is placed below ITO layer 230. Because ITO layer 230 is conductive, electrostatic charge built up on glass layer 211 can be discharged by connecting ITO layer to a ground in a known manner. This can advantageously prevent damage to capture sensor 200. Image capture sensor can be fabricated in substantially the same manner as image capture sensor 100 except that ITO layer 230 is formed over glass layer 211 and insulating layer 232 is formed over ITO layer 230 prior to forming light shielding layer 222 over insulating layer 232.

[0024] A third embodiment of an image capture sensor in accordance with the present invention is shown in Figure 6. Image capture sensor 300 has substantially the same structure as capture sensor 100. Specifically, capture sensor 300 includes a light sensing unit 312, which is substantially the same and light sensing unit 112, and switching unit 313, which is

substantially the same as switching unit 113, formed between an insulating layer 316 and a passivation layer 318. However, above insulating layer 316 capture sensor 300 includes a substrate layer 330 having a plurality of fiber-optic strands 330a running in a direction perpendicular to a surface of substrate layer 330. Preferably, the diameter of the fiber-optic strands 330a forming substrate layer 330 is from about 4 μm to about 8 μm in diameter and more preferably about 6 μm in diameter, though larger or smaller diameters can also be used. Substrate layer 330 can be formed from glass fiber optic strands 330a or fiber optic strands of other substantially transparent materials including polymers. Fiber optic sheets which can be used to form substrate layer 330 are known in the art and available from, for example, Schott Fiber Optics of Southbridge MA.

[0025] In operation, as shown in Figure 6, a fingerprint 320 including a fingerprint ridge 322 to be imaged is placed on an exposed surface of fiber-optic layer 330. Incident light from backlight 320, which can be substantially the same as backlight 120 of capture sensor 100, passes into fiber-optic layer 330 and can either directly pass through fiber-optic layer 330 as shown by arrow 340, or pass through fiber-optic layer 330 by undergoing total internal reflection (TIR) from the sides of a fiber-optic strand 330a, as shown by arrow 342. In either case, if the incident light from backlight 320 strikes a fingerprint ridge 322, it will scatter back through fiber-optic layer 330 either directly or, as shown by arrow 344, undergoing TIR to reach photosensitive layer 312-P of light sensing unit 312. Because light scattered from a fingerprint ridge 322 can undergo total internal reflection to pass through fiber-optic layer 330, fiber-optic layer 330 can be relatively thicker than a glass layer such as glass layer 111 without degrading the performance of capture sensor 300. As such, fiber-optic layer is preferably 0.8 mm to 1.0 mm but may be either thicker or thinner. Because, as described above, fiber-optic layer can be relatively thick, a fiber-optic layer such as fiber-optic layer 330 can provide relatively more protection for an image capture sensor such as image capture sensor 300. Image capture sensor 300 can be fabricated in substantially the same manner as image capture sensor 100 except that fiber-optic layer 330 is used in place of glass layer 111. It is also considered that glass layer 211 of image capture sensor 200 be replaced by a fiber-optic layer such as fiber-optic layer 330.


CLAIMS

What is claimed as new and desired to be protected by Letters Patent of the United States is:

1. An image capture sensor including:
 - a light detection transistor including a light sensitive layer which conducts electricity in response to detection of a predetermined amount of light;
 - a switch interconnected to the light detection transistor and responsive to detection of light by the light detection transistor;
 - a glass substrate layered over the light detection transistor and switch and upon which a patterned object to be imaged is placed.
2. The device of claim 1 further including a capacitor that interconnects the light detection transistor and the switch.
3. The device of claim 2 wherein the switch is a transistor switch.
4. The device of claim 3 including a first light shielding layer that reduces the amount of light to which a first surface of the light sensitive layer is exposed.
5. The device of claim 4 wherein the glass substrate includes a fiber-optic layer having fiber-optic strands formed perpendicularly to a surface of the fiber-optic layer on which an object to be imaged is placed.
6. The device of claim 5 wherein the object to be imaged is a fingerprint.
7. The device of claim 6 including a backlight positioned such that the light sensitive transistor and switch are positioned between the glass substrate and the backlight.
8. The device of claim 4 including a conductive layer and an insulating layer, the conductive layer formed over the glass substrate and the insulating layer formed over the conductive layer such that both the conductive layer and the insulating layer are between the glass substrate and the light sensing transistor.

9. The device of claim 7 wherein the object to be imaged is a fingerprint.
10. A method of imaging a patterned object including:
providing an image capture sensor having:
 - a light detection transistor including a light sensitive layer which conducts electricity in response to detection of a predetermined amount of light;
 - a switch interconnected to the light detection transistor and responsive to detection of light by the light detection transistor;
 - a glass substrate layered over the light detection transistor and switch; andplacing the object to be imaged on the glass substrate.
11. The method of claim 10 wherein placing the object to be imaged on the glass substrate includes placing a fingerprint to be imaged on the glass substrate.
12. The method of claim 11 wherein providing an image capture sensor includes providing an image capture sensor having a glass substrate including fiber-optic strands.
13. The method of claim 11 wherein providing an image capture sensor includes providing an image capture sensor having a conductive layer formed over the glass substrate and an insulating layer formed over the conductive layer.
14. An image capture sensor including:
 - a light detection transistor including a light sensitive layer which conducts electricity in response to detection of a predetermined amount of light;
 - a switch interconnected to the light detection transistor and responsive to detection of light by the light detection transistor;
 - a substrate layered over the light detection transistor and switch and upon which a patterned object to be imaged is placed, the substrate including fiber-optic strands.
15. The device of claim 14 further including a capacitor that interconnects the light detection transistor and the switch.

16. The device of claim 15 wherein the switch is a transistor switch.
17. The device of claim 16 including a first light shielding layer that reduces the amount of light to which a first surface of the light sensitive layer is exposed.
18. The device of claim 17 wherein the fiber-optic strands are formed perpendicularly to a surface of the substrate.
19. The device of claim 18 wherein the object to be imaged is a fingerprint.



7
12




Fig 2





Fig. 3






Fig. 5




Fig. 6

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 March 2004 (04.03.2004)

PCT

(10) International Publication Number
WO 2004/019382 A3

(51) International Patent Classification⁷: **G06K 9/00**,
H01L 27/00, 29/15

(21) International Application Number:
PCT/US2003/026428

(22) International Filing Date: 21 August 2003 (21.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/405,604 21 August 2002 (21.08.2002) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): SECUGEN CORPORATION [US/US]; 2356 Walsh Ave., Santa Clara, CA 95051 (US).

Published:
— with international search report

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): KIM, Jee-Hoon [KR/US]; 20380 Stevens Creek Boulevard #204, Cupertino, CA 95014 (US). AKIBA, Shigetaka [JP/JP]; #419, 3-11-31, Ikejiri, Setagaya-ku, Tokyo 154-0001 (JP). LEE, Dong, Won [KR/US]; 20700 Fourth Street, Saratoga, CA 95070 (US).

(88) Date of publication of the international search report:
17 June 2004

(15) Information about Correction:
Previous Correction:
see PCT Gazette No. 19/2004 of 6 May 2004, Section II

(74) Agents: HODDER, Douglas, G. et al.; Morrison & Foerster LLP, 755 Page Mill Road, Palo Alto, CA 94304 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 2004/019382 A3

(54) Title: TFT SENSOR HAVING IMPROVED IMAGING SURFACE

(57) Abstract: Disclosed is an image capture sensor (100) including a light detection transistor (112) having a light sensitive layer which conducts electricity in response to detection of a predetermined amount of light and a switch (113) interconnected to the light detection transistor and responsive to detection of light by the light detection transistor. A glass substrate (111) is layered over both the light detection transistor and switch. The glass substrate provides a durable and smooth surface upon which a patterned object to be imaged is placed.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US03/26428

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G06K 9/00; H01L 27/00, 29/15

US CL : 382/124; 250/208.1; 257/72

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 382/115,116,124,125,126; 250/208.1,214R,553.5; 257/59,72,350,E29.151,E51.005; 345/92; 385/130

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
Please See Continuation Sheet**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2002/0027188 A1 (YOON et al.) 07 March 2002 (07.03.2002), page 1.	1-19
Y	US 2001/0033254 A1 (FUTUDSATO et al.) 25 October 2001 (25.10.2001), page 4 and figure 1.	1-13
Y	US 4,932,776 A (DOWLING, JR. et al.) 12 June 1990 (12.06.1990), columns 3-4	5-7,12,14-19
Y	US 5,907,627 A (BORZA) 25 May 1999 (25.05.1999), column 1.	1-13
A	YOUNG ET. AL., "Novel Fingerprint Scanning Arrays Using Polysilicon TFT's on Glass and Polymer Substrates" (Electron Device Letters, IEEE, Volume: 18, Issue: 1, Jan. 1997, pages 19-20.	1-19

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

02 March 2004 (02.03.2004)

Date of mailing of the international search report

26 MAR 2004

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

Facsimile No. (703)305-3230

Authorized officer

Amelia Au

Telephone No. 703-306-0377

INTERNATIONAL SEARCH REPORT

PCT/US03/26428

Continuation of B. FIELDS SEARCHED Item 3:

IEEE

search terms: tft, fingerprint, image sensor